

DS-2CE56C2P(N)-VFIR3



Key Features

- 1/3" PICADIS
- 720TVL horizontal resolution
- 2.8 – 12mm vari-focal lens
- True Day/Night
- Up to 40m IR distance
- Smart IR, high dynamic range
- IP66 weatherproof
- Wide operating temperature range

Specification

Model	DS-2CE56C2P(N)-VFIR3
Parameter	720TVL PICADIS Vari-focal IR Bullet Camera
Camera	
Image Sensor	1/3" PICADIS
Signal System	PAL/NTSC
Effective Pixels	1280 (H) × 960 (V)
Min. Illumination	0.1Lux @ (F1.2,AGC ON) ,0 Lux with IR 0.14Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	PAL: 1/25 s to 1/25,000 s NTSC: 1/30 s to 1/30,000 s
Lens	2.8 - 12 mm @ F1.4 Angle of view: 80° - 27.2°
Lens Mount	φ14
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day & Night	ICR
Horizontal Resolution	720 TVL
Synchronization	Internal synchronization

Video Output	1Vp-p composite output (75 Ω/BNC);
S/N Ratio	More than 62 dB
General	
Working Temperature/Humidity	-40 °C - 60 °C (14 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 7.5 W
Ingress Protection	IP66
IR Range	40m
Dimension	Φ130.54 × 102.4mm (Φ5.1" × 4")
Weight	

Order Models

DS-2CE56C2P-VFIR3

DS-2CE56C2N-VFIR3

Dimension

